


Ken-Tool®

TRUCK TIRE HAMMERS



HAMMER WITH FIBERGLASS HANDLE.

PART NO.	MFR. NO.	OVERALL LENGTH
TG-11	35429	32"
TG-11EH	35229	32" Rpl. Handle



HAMMER WITH WOOD HANDLE

PART NO.	MFR. NO.	OVERALL LENGTH
T-11E	35329	30"
T-11EH	35129	30" Rpl. Handle

*Other sizes & replacement handles available

DOUBLE END TRUCK WRENCHES

STANDARD



PART NO.	MFR. NO.	SOCKET SIZES
TR1	32501	1 1/8", 13/16", sq.
TR98	32508	1 1/2", 13/16" sq.
TR2	32502	1", 1 1/4", 5/8" sq.
TR9	32509	1 1/4", 1 1/16"


TRUCK WRENCH HANDLE

Handle is extra long for increased leverage and heat treated for extra strength

PART NO.	MFR. NO.	LENGTH	HEX
TR-5	32318	22"	3/4"

4-WAY WRENCHES

PASSENGER CAR



PART NO.	MFR. NO.	LENGTH
Socket sizes: 3/4", 13/16", 7/8", 15/16"		
T-57	35657	23"

LIGHT TRUCK



PART NO.	MFR. NO.	LENGTH
Socket sizes: 7/8", 15/16", 1", 1 1/16"		
T-90	35690	25"

HEAVY DUTY TRUCK FOUR-WAY

PART NO.	MFR. NO.	LENGTH
Socket sizes: 1 1/16", 1 1/4", 1 1/2", 13/16" sq.		
T-95	35695	27 1/2"

*Other sizes available

TUBELESS TIRE TOOLS

Designed for mounting and demounting tubeless tires. Hand forged chrome nickel steel. Use in pairs.



PART NO.	MFR. NO.	LENGTH
T-45A	34645	37"

HEAVY DUTY TUBELESS TRUCK IRON

Stock is 7/8" for extra strength, length is 41" for extra leverage. Use in pairs.

PART NO.	MFR. NO.	LENGTH
T-45 HD	34647	41"

MOUNT/DEMOUNT TIRE SPOONS

STRAIGHT SPOON TIRE IRONS



PART NO.	MFR. NO.	LENGTH	DIA.
T-19	32119	24"	11/16"
T-19A	33219	30"	11/16"
T-38	33238	30"	7/8"

CURVED SPOON TIRE IRONS



PART NO.	MFR. NO.	LENGTH	DIA.
T-2X	32102	18"	11/16"
T-20A	33220	30"	11/16"
T-39	33239	30"	7/8"

TRUCK LOCK RING REMOVERS

Designed especially for Firestone RH and TI rims.



PART NO.	MFR. NO.	LENGTH	DIA.
T-23	32123	24"	11/16"

Designed especially for Firestone RH and RI rims

T-23A	33223	30"	11/16"
-------	-------	-----	--------

Combination ring tool T-23B with flat tapered end. Ideal for all around ring and rim work.



PART NO.	MFR. NO.	LENGTH	DIA.
T-23B	33224	23 1/2"	11/16"

Combination ring remover. Curved end is shaped to remove full circle lock rings. Avoids distorting rings.



PART NO.	MFR. NO.	LENGTH	DIA.
T-22	32122	18"	5/8"

For servicing 50 wide base rims.



PART NO.	MFR. NO.	LENGTH	DIA.
T-25	32125	18"	5/8"

For removal of continuous side rings on two piece truck rims



PART NO.	MFR. NO.	LENGTH	DIA.
T-27A	32128	18"	5/8"


Aids in removing and replacing lock rings on all Budd, Ford, Chevrolet, and GMC wheels.



PART NO.	MFR. NO.	LENGTH	DIA.
T-48A	34648	37"	3/4"

BUDD NUT WRENCHES

Holds outer cap nut while turning inner nut on Budd and Ford wheels.



PART NO.	MFR. NO.	SIZE
TX-9	30609	1 1/2" and 38mm
TX-10	30610	35mm
TX-12	30612	41mm