


**VALVE CORES**

High quality Valve Cores include standard Short Cores, Heat-Resistant Cores, Long Cores and Large Bore Cores.

STOCK NO.	DESCRIPTION	TR NO.	UNITS/BOX
A100-VC1	Short Heat-Resistant Valve Core	C1	100
A144	0.302" Large Bore Valve Core, 32-T	C2	10

**VALVE CAPS**

An often overlooked way to keep tires properly inflated, we offer a wide-range of standard and large bore valve caps.



STOCK NO.	DESCRIPTION	TR NO.	UNITS/BOX
A100-VC2	Fork-Type Standard Metal Cap	VC2	100
A100-VC3	Dome-Type Standard Metal Cap	VC3	100
A100-VC8	Dome-Type Standard Plastic Cap	VC8	1000
A100-VC12	Skirted Dome-Type Heat-Resistant Metal Cap	VC3	100
A148	Fork-Type Large Bore Valve Cap	VC6	10
A149H	Hex Head Large Bore Valve Cap	VC7	10


**PRESSURE GAUGES & INFLATORS**

**AIR PRESSURE & TREAD DEPTH GAUGES**



STOCK NO.	DESCRIPTION
GA105	Passenger/Light Truck Pressure Gauge: 10-50 psi low pressure, durable nylon indicator bar reads in one pound increments, high impact chrome body, complete with pocket clip and deflator pin
GA135S	Dual Head Truck Pressure Gauge: 10-120 psi high pressure, 6" extension on all-chrome body, durable nylon indicator bar reads in two pound increments, complete with metal ring
GA150	Dual Head RV Pressure Gauge: 20-120 psi high pressure, durable nylon indicator bar reads in two pound increments, high impact chrome body, complete with pocket clip
GA190	Tread Depth Gauge: durable all-chrome construction, wide base, reads 0" to 1" in 1/32" increments, complete with pocket clip

**IN-LINE TIRE INFLATORS**



STOCK NO.	DESCRIPTION
I405-3M	In-Line Tire Inflator: easy-to-read three-sided brass indicator bar calibrated from 0 to 120 psi in two pound increments, convenient chuck and inflator valve for easy bleeding of over-inflated tires, complete with 36" safety hose with clip-on valve chuck

**AIR CHUCKS**



STOCK NO.	DESCRIPTION	UNITS/BOX
CH305	Ball Chuck: 1/4" female fitting	10
CH315	Ball Chuck: clip-on type, not flow through (for direct air lines)	5
CH318	Screw-in Air Chuck Clip	5
103753	Ball Chuck: clip-on type, flow through (for tire changers & inflator gauges)	5
CH330LO	Lock-on Dual Head Chuck	5
CH340	Grip-on Lock Type Chuck, not flow through (for direct air lines)	5

**AIR HOSE & ACCESSORIES**




**AIR LINE COUPLERS & NIPPLES**

Cadmium-plated hardened steel air line couplers and nipples are designed for long service life. All couplers feature a positive locking, sliding sleeve to prevent accidental uncoupling. Tru-Flate, ARO, Lincoln and Milton types available.



STOCK NO.	DESCRIPTION	THREAD
CO-101	1/4" Tru-Flate Male Coupler	1/4"
CO-103	1/4" Tru-Flate Female Coupler	1/4"
CO-105	1/4" Tru-Flate Female Ring Sleeve Coupler	1/4"
NI-102	1/4" Tru-Flate Male Nipple	1/4"
NI-104	1/4" Tru-Flate Female Nipple	1/4"
NI-106	1/4" Tru-Flate .302-32 Female Nipple, with standard valve cap thread	1/4"
CO-107	3/8" Tru-Flate Male Coupler	3/8"
CO-109	3/8" Tru-Flate Female Coupler	3/8"
12-604	3/8" Tru-Flate Male Nipple	3/8"
12-612	3/8" Tru-Flate Female Nipple	3/8"
13-704	1/2" Tru-Flate Male Coupler	1/2"
CO-111	1/2" Tru-Flate Female Coupler	1/2"
NI-112	1/2" Tru-Flate Male Nipple	1/2"
NI-D3F	1/2" Tru-Flate Female Nipple	1/2"
12-702	1/2" Tru-Flate Male Nipple, with 3/8" NPT	3/8"
13-324	1/4" ARO Male Coupler	1/4"
CO-501	1/4" ARO Female Coupler	1/4"
12-324	1/4" ARO Male Nipple	1/4"
NI-502	1/4" ARO Female Nipple	1/4"
CO-702	1/4" Lincoln Male Coupler	1/4"
CO-701	1/4" Lincoln Female Coupler	1/4"
NI-702	1/4" Lincoln Male Nipple	1/4"
NI-704	1/4" Lincoln Female Nipple	1/4"
13-224	1/4" Milton Male Coupler	1/4"
CO-201	1/4" Milton Female Coupler	1/4"
NI-202	1/4" Milton Male Nipple	1/4"
NI-204	1/4" Milton Female Nipple	1/4"

**REINFORCED AIR HOSE**



Two-ply heavy duty, non-kink Reinforced Air Hose can take the worst punishment: oil, grease, abrasion and extreme temperatures. Built to handle pressures up to 250 psi. Length comes complete with male pipe thread on both ends.

STOCK NO.	DESCRIPTION	HOSE ID
38-25HD	25' Reinforced Air Hose with 3/8" Male Ends	3/8"
38-50HD	50' Reinforced Air Hose with 3/8" Male Ends	3/8"
12-25B	25' Reinforced Air Hose with 1/2" Male Ends	1/2"
12-50HD	50' Reinforced Air Hose with 1/2" Male Ends	1/2"

**PERMA COIL® RETRACTING AIR HOSE**



Bright yellow coiled retracting air hose is extremely durable and resists damage from oil, chemicals and abrasion. Easy-to-see bright color helps eliminate accidents. All units include a brass 360° swivel male connector.

STOCK NO.	DESCRIPTION
23-404	50' Perma Coil Air Hose, 1/4"
23-413	25' Perma Coil Air Hose, 3/8"

Note: Air line regulators, filters, and water separators also available.



**WHEEL BALANCING WEIGHTS  
PASSENGER CAR & LIGHT TRUCK WEIGHTS**

Our wheel balancing weights product line includes dry polymer-coated and non-coated clip-on weight styles, non-coated and chrome Tape-A-Weights™, and accessories and tools to handle virtually any wheel balancing application. BADA, the wheel weight supplier to NASCAR®, provides more solutions than any other company in the wheel balancing industry.

STYLE	DESCRIPTION
<b>T-THINLINE</b>	Uncoated All import and domestic passenger cars, 1/2 ton trucks, mini pickups and vans with standard .125" flange. NASCAR sanctioned. 20 sizes: .25 to 6 oz
<b>ALC</b>	Aluma-Guard™ Coated Domestic (GM, Ford & Chrysler) 12 sizes: .25 to 3 oz.
<b>ALCMC</b>	Aluma-Guard™ Coated Domestic (GM, Ford & Chrysler) 12 sizes: .25 to 3 oz.
<b>ALCLH</b>	Aluma-Guard™ Coated Newer Chrysler 12 sizes: .25 to 3 oz.
<b>TTC</b>	Aluma-Guard™ Coated New Domestic Lt. Truck (GM, Ford, & Chrysler) 12 sizes: .25 to 3 oz.
<b>ALCIW</b>	Aluma-Guard™ Coated European, Subaru 11 sizes: 10g to 60g
<b>ALCTW</b>	Aluma-Guard™ Coated European, Subaru, & Mitsubishi 12 sizes: .25 to 3 oz.
<b>ALCFN</b>	Aluma-Guard™ Coated Newer Japanese 12 sizes: 5g to 60g
<b>ALCEN</b>	Aluma-Guard™ Coated Mercedes & older Japanese 11 sizes: (in 5g incr.) 10g to 60g
<b>2101</b>	Tape-A-Weights Compact weight sections to also fit motorcycle applications. 30 pieces, .5 oz. segments, 3/8" x 12", 360 segments



**TRUCKS & RV WEIGHTS - ALLOY & STEEL WHEELS**

STYLE	DESCRIPTION
<b>BTS</b>	Uncoated All 3/4 and 1 ton trucks with 13", 15" and 16" two-piece rims; 16.5" x 6.00", 6.75", 8.25" and 9.75" tubeless wheels. 10 sizes: .50 to 6 oz.
<b>BTLM</b>	Uncoated 1 1/2 to 2 ton medium-duty trucks & buses with tube type wheels; Firestone R, DT, and LB; Goodyear wheels L, LW and M. Sizes: 9 sizes: 2 to 16 oz.
<b>BTRC</b>	Uncoated Tubeless curved flange truck wheels like Firestone Radial I Commander, Budd, Firestone, Goodyear strip-steel wheels. 8 sizes: 2 to 14 oz.
<b>BTLT</b>	Uncoated Used on "section" type, straight flange, tubeless wheels' Goodyear Super Single; Budd 7.50" and 8.25" wheels with Firestone or Goodyear discs. 9 sizes: 2 to 16 oz.
<b>BTCAL</b>	Aluma-Guard™ Coated Used on both open side (inside flange) and disc side (lug nut-side flange) for ALCOA and firestone aluminum truck wheels. 4 sizes: 3 to 8 oz.
<b>BTST</b>	Uncoated Budd DUO 16" x 5.50" split-ring wheels, RVs, 3/4 and 1 ton trucks with thick flange wheels that prohibit use of BTS weights. 6 sizes: 2 to 8 oz.

**STEEL WHEEL WEIGHTS FOR P-FLANGE & MC-FLANGE WHEELS**

STYLE	DESCRIPTION
<b>PFE</b>	Application: P-Flange Steel Wheels (Passenger Cars and Light Trucks) All styles available in 1/4 oz. to 3 oz. sizes.
<b>MCFE</b>	Application: MC-Flange Steel Wheels, Domestic Passenger Cars & Light Trucks (GM, Ford, Chrysler) All styles available in 1/4 oz. to 3 oz.



**EQUAL TIRE BALANCING FORMULA**

**Continuous Balance... Every Tire, Every Wheel Position, Every Time!**

**No More Vibration & Uneven Treadwear**



Equal is a revolutionary dry balancing formula that provides a continuous balance to the tire and wheel assembly. Easy to install on or off the vehicle. Especially effective for difficult to balance aluminum rims.

ORDER NO.	FOR TIRE SIZE	USE PACKAGE SIZE
A12	1200 R22.5	A
B10	10.00 R20-275/80 R24.5	B
C8	900 R20- 245/75 R22.5	C
D6	800 R19.5-245/70 R19.	D
E4	800 R17.5-225/75 R17.5	E
F2	215/85 R16-9.50-R16.5	F

For best results, use a valve stem filter extension when using Equal. Install Equal through the valve stem.

**Recommended Accessories**


DESCRIPTION
• Portable Applicator • Valve Stem Filter- Nickel Plated • Valve Stem Filter- Brass



## REPLACEMENT LUG NUTS



PART NO.	DESCRIPTION
41128	12 x 1.25 Chrome Bulge Acorn - 3/4 Hex
41138	12 x 1.50 Chrome Bulge Acorn - 3/4 Hex
41148	14 x 1.55 Chrome Bulge Acorn - 3/4 Hex
41178	7/16 " Chrome Bulge Acorn - 3/4 Hex
41188	1/2 " Chrome Bulge Acorn - 3/4 Hex
71128	12 x 1.25 Chrome Acorn - 13/16 Hex
71138	13 x 1.50 Chrome Acorn - 13/16 Hex
71178	7/16" Chrome Acorn - 13/16 Hex
71188	1/2" Chrome Acorn - 13/16 Hex



PART NO.	DESCRIPTION
91138	12 x 1.50 Chrome Bulge Acorn - 13/16 Hex
91148	14 x 1.50 Chrome Bulge Acorn - 13/16 Hex
91178	7/16" Chrome Bulge Acorn - 13/16 Hex
91188	1/2" Chrome Bulge Acorn - 13/16 Hex



5844	12 x 1.25 Acorn Style OE Lug Nut - 21mm Hex
5845	12 x 1.50 Acorn Style OE Lug Nut - 19mm Hex
5580R	7/16" Acorn Style OE Lug Nut - 3/4 Hex
5581R	1/2" Acorn Style OE Lug Nut - 3/4 Hex
5586R	1/2" Acorn Style OE Lug Nut - 13/16 Hex

5120	1/2"x 20 Acorn Style OE Lug Nut - 7/8 Hex - Outside Threaded for Nut Covers
5014	14 x 1.5 Acorn Style OE Lug Nut - 7/8 Hex - Outside Threaded for Nut Covers
5916	9/16"x 18 Acorn Style OE Lug Nut - 7/8 Hex - Outside Threaded for Nut Covers



PART NO.	DESCRIPTION
39946	5/8" 2-Piece Swivel Flanged Lug Nut - 1-1/16" Hex
139987	9/16" 2-Piece Swivel Flanged Lug Nut - 1.050 Hex
39913	14mm x 20 2-Piece Swivel Flanged Lug Nut - 1-1/16" Hex
139698	14mm x 1.5 2-Piece Swivel Flanged Lug Nut - 1.050 Hex

## WHEEL NUT AND STUD REMOVING KIT




For removing 13/16" Budd wheel inner cap nuts, 3/4" and 5/8" lug studs. Kit includes Drive-On Tool, 13/16" sq. 1 1/8" dia., 3/4", and 5/8" Rib Nuts, and Drift Pin.

PART #	DESCRIPTION
5205	Triple Duty Kit

## REPLACEMENT RIB NUTS


Order as required.



PART #	DESCRIPTION
5206	1 1/8" dia. (13/16" square head) Rib Nut
5207	3/4" Rib Nut

## 5/8" AND 3/4" STUD SETTERS

Simply thread STUD SETTER on. Use impact or 4-way wrench to install stud.




ORDER NO.	DESCRIPTION
5833	5/8" Wheel Stud Setter - uses 1 1/8" hex socket
5834	3/4" Wheel Stud Setter - uses 1 1/4" hex socket



## CHROME NUT COVER REMOVER

Removes and installs chrome wheel nut covers without scratching or damage. Adjustable. Formed steel jaws with Non-Mar protective coating.

ORDER NO.	DESCRIPTION
M9700	Chrome Nut Remover




## MARKAL® PAINTSTIK®

### Permanent Paint

Permanent, waterproof and fadeproof. Marks on wet tires or tires covered with mold lubricant. Withstands vulcanizing and retreading temperatures. Also marks on wood, plastic, glass, etc. Nontoxic, contains no lead. Sold 12 per box.

MFR. NO.	COLOR
MHKPS	White




## AUTO & LIGHT TRUCK BOLT PATTERN GAUGE

Easily identify rim sizes. Gauge fits over disc or drum studs to accurately measure bolt patterns. Mag wheels are measured by fitting the gauge into 2 lug holes. To measure wheels with conical holes use the 2 conical adapters. Kit includes 4 and 5 lug hole gauges.

PART #	DESCRIPTION
2002	Wheel Gauge

## WHEEL GUARDS

- Protect Steel and Aluminum Wheels
- Prevent Corrosion



Wheel Guard is a black nylon separator plate approximately 1/32" thick that is placed between the hub and the wheel or between dual wheels. We recommend the wheel guard be used to prevent corrosion and wear between surfaces. Use with both steel and aluminum wheels.

MFR. NO.	APPLICATION	DIAMETER STUD
5901	10 HOLE 11 1/4" bolt circle	1 1/8" and 7/8"
5902	10 HOLE 11 1/4" bolt circle	3/4"
5903	10 HOLE 285.75mm bolt circle	22mm
7902	8 HOLE 275mm bolt circle	20mm
7903	8 HOLE 6.5" / 170mm bolt circle	light truck applications
7904	8 HOLE 225mm bolt circle	light truck applications



## BEAD SEATER - PART# BLASTER

- Set Tubeless Beads Instantly- Every Time!
- Eliminate Personal Injuries
- **USE NO ETHER USE NO TIRE GREASE USE NO TIRE COMPRESSOR BANDS**
- A SAFE AND EASY TIRE INFLATING DEVICE.
- COULD PAY FOR ITSELF IN 24 HOURS!
- Completely Portable- weighs only 25 lbs.
- Carry in one hand- Road & Shop use
- If your man can turn a key, then he can now seat a Bead *Instantly*
- Set all tires from the smallest car up to 17.5x25
- Golf Cart Tires • Race Car Tires